

Data Sheet for Model No. LN033048AH

: SCOPE

This Specification describes the requirements of the lithium-ion rechargeable battery supplied by
HONG KONG BATTERIES Under GB/T18287-2000



: BASIC CHARACTERISTICS

2.1	Battery Type	LN033048AH
2.2	Material of Case	Alumimium Case
2.3	Nominal Voltage	3.7 V
2.4	Nominal Capacity	550 mAh
2.5	Internal Resistance	< 60 mΩ
2.6	Discharge Cut-off Voltage	2.75V (Per Cell)
2.7	Maximum Charge Current	1.0C ~ 1.5C
2.8	Maximum Discharge Current	1.5C
2.9	Maximum Charge Voltage	4.2V
2.10	Charge method	CC/CV (constant current/constant voltage)
2.11	Dimension	Thickness: 3.9 ±0.1mm Width: 30 ±0.2mm Height: 48 ±0.5 mm
2.12	Weight	About 12.6 (g) only for Reference.
3.13	Operating Temperature:	Charging Temperature: 0~45°C Discharging Temperature: -20~60°C
3.14	Storage Temperature	1 month -20~60°C 3 month -20~45°C 1 year -20~25°C
3.15	Relative Humidity	65±20%
3.16	Visual Requirements	Defects, such as scratches, flaws, dirty spots, rust, deformation, discoloration, leakage, etc., which damages commercial values shall not be presented.
3.17	Voltage of shipment	3.70V ~ 3.75V
3.18	UL is pending for this item. Contact us for detail	
3.19	HkbiL reserves the right to alter or amend the design & specification without prior notice.	

: TECHNICAL REQUIREMENTS

Testing Conditions (unless otherwise specified)

Temperature: :15~35°C
Relative Humidity : 45%~75%
Atmospheric pressure: :86~106Kpa


Data Sheet for Model No. LN033048AH

: RECOMMENDED PROTECTION FUNCTIONS

The standard charge method is CC/CV (constant current/constant voltage)

NO	Device	Items	Requirements
1	Charger	Charge termination voltage	$4.200 \pm 0.049V$
2	Protection SEIKO Functions (For reference)	Excess Charge detection voltage.	$4.275 \pm 0.025V$
3		Excess Charge release voltage.	$4.175 \pm 0.050V$
4		Discharge termination voltage.	$3.00 \pm 0.10V$
5		Excess discharge detection voltage.	$2.3 \pm 0.08V$
6		Excess discharge release voltage	$2.4 \pm 0.10V$
7		Excess current detection value	$2.7 \pm 0.2A$

Bare Cell-Dimensions Without Tube (mm)



(mm)	Thickness	Width	Length
Bare cell	3.9	30	48
Battery Pack	(1) & (3) + positive / (2) - Negative		

Note:

- Use a specified charger.
- Do not throw the battery into fire, or heat.
- Do not short-circuit the battery terminals.
- Do not disassemble the battery.

